

Specification sheet			
Product description	Belling BEL GHU753RI STA Built-In Gas Hob 75cm Stainless steel	Belling BEL GHU753CI STA Built-In Gas Hob 75cm Stainless steel	Belling BEL GTG753RI BLK Built-In Gas Hob 75cm Glass
Brand	Belling	Belling	Belling
SKU Code	444411638	444411639	444411640
SKU Description	BEL GHU753RI STA	BEL GHU753CI STA	BEL GTG753RI BLK
EAN	5052263116382	5052263116399	5052263116405
Product Type	Built-In	Built-In	Built-In
Category	Gas Hob	Gas Hob	Gas Hob
Size	75cm	75cm	75cm
Finish	Stainless steel	Stainless steel	Glass
Technical Specifications			
Hob summary			
Width	75cm	75cm	75cm
No of burners/elements	5	5	5
Hob fuel type	Gas	Gas	Gas
Hot plate material	Stainless steel	Stainless steel	Glass
Pan support type	Matt black enamel coated steel	Cast Iron	Matt black enamel coated steel
Ignition type	Automatic	Automatic	Automatic
Wok burner	Yes	Yes	Yes
Burners & power			
Burner/element 1 (kW)	Large (3.6)	Large (3.6)	Large (3.6)
Burner/element 2 (kW)	Large (3.0)	Large (3.0)	Large (3.0)
Burner/element 3 (kW)	Medium (1.75)	Medium (1.75)	Medium (1.75)
Burner/element 4 (kW)	Medium (1.75)	Medium (1.75)	Medium (1.75)
Burner/element 5 (kW)	Small (1.0)	Small (1.0)	Small (1.0)
Burner/element 6 (kW)			
Controls			
Control type and location	Rotary, Front Center	Rotary, Front Center	Rotary, Front Center
Style of knob - colour & type	Chrome	Chrome	Chrome
Safety features			
Flame safety device	Yes	Yes	Yes
Energy			
Gas Efficiency Burner 1	55.52	55.52	60.58
Gas Efficiency Burner 2	63.21	63.21	/
Gas Efficiency Burner 3	/	/	61.25
Gas Efficiency Burner 4	56.39	56.39	63.3
Gas Efficiency Burner 5	59.11	59.11	62.54
Gas Efficiency Burner 6			
Total Hob Gas Efficiency	59%	59%	62%
Accessories			
LPG Conversion kit (available separately)	Yes	Yes	Yes
Installation			
Gas type	NG (G20) / LPG (G30)	NG (G20) / LPG (G30)	NG (G20) / LPG (G30)
Gas Category	I12H3+	I12H3+	I12H3+
Gas inlet type	1/2" BSP Female Coupler	1/2" BSP Female Coupler	1/2" BSP Female Coupler
Gas inlet position	Bottom Rear RH	Bottom Rear RH	Bottom Rear RH
LPG convertible	Yes	Yes	Yes
Hard wired	Yes	Yes	Yes
Terminal block position	Base Rear	Base Rear	Base Rear
Power supply	220V-240V	220V-240V	220V-240V
Supply frequency	50-60Hz	50-60Hz	50-60Hz
Phase (single or 3)	single	single	single
Lead length (m)	1	1	1
Maximum rating	N/A	N/A	N/A
Total electrical power load (kW)	0.004	0.004	0.004
Total gas power load (kW)	11.1	11.1	11.1
Fuse size (A)	5	5	5
Fitted 3 pin plug	Yes	Yes	Yes
Dimensions			
Boxed Dimensions			
Height (mm)	166	166	166
Width (mm)	818	818	818
Depth (mm)	574	574	574
Weight (kg)	11.9	15.9	14.2
Product Dimensions			
Height (mm)	101	101	97
Width (mm)	750	750	750
Depth (mm)	510	510	510

Weight (kg)	9.7	13.2	12
Cutout Dimensions			
Height (mm)	480	480	480
Width (mm)	560	560	560
Depth (mm)	N/A	N/A	N/A
Product Supply Information			
Country of origin	CHINA	CHINA	CHINA
Warranty period (standard)	1 Year	1 Year	1 Year