	06/09/2024	
Speci	fication sheet	
Brand a	nd Model	
	Brand	Belling
	Sub-brand Model	Farmhouse BEL RCA FARMHOUSE 100E
Summar	y Product Type	100cm Electric Ceramic Range Cooker
	Short Product Description	100cm Electric range cooker with a 5 zone ceramic hob +1 warming zone, fanned main oven, conventional second oven, separate grill, and storage compartment
		Belling Range Cookers have been at the heart of UK homes for more than a century, and
		they'll be there for you for many years to come. At 100cm wide, this mid-size Farmhouse electric model is the versatile choice for many kitchens.
		Within its classic frame, there's a huge 194 litres of cooking capacity and a host of features designed to make cooking simple. You can choose between two electric ovens: a conventional
	Long Product description	electric second oven, and the fanned main electric oven with a variety of different functions. This includes the AirFry function and tray, which puts all the time-saving benefits of this
		appliance back into your oven (freeing up space on your countertop.) Then up on the easy-clean ceramic glass hob, you'll find five different cooking zones and a
		dedicated warming zone, giving you the space to sauté, simmer and sizzle.
		You can rely on this Belling Range Cooker to help you make more memories around the dinner table.
		When it comes to the Farmhouse Collection, traditional is the operative word. Charming
	Range Overview	traditional looks, combined with Belling's long-standing reputation for reliability, gives you a cooker that can take anything you throw at it and still turn out a perfect performance.
Key P	roduct Benefits	
	Feature 1 Feature 2	2 Ovens plus separate grill with 199L Total Capacity 5 Zone ceramic hob plus warming zone
	Feature 3	Fanned main electric oven with clever features including AirFry
	Feature 4 Feature 5	Conventional electric second oven AirFry function & Tray
	Feature 6	Make cleaning easier with Easy-Clean enamel
	Feature 7 Feature 8	Separate variable electric grill Maxi-Clock Programmer
	Feature 9 Feature 10	Slow Cook Function
		Storage Compartment
	Product Type Integrated or freestanding	Range Cooker Freestanding
	Fuel	Electric Ceramic
	Number of ovens Warranty period	2 3 Years Parts & Labour
Hob layo		
		3 6
		1 4
		2 5
Cavity la	yout	
		1
		3
		2 4
Hob		
	Hob summary	5 Ceramic Zones + 1 Warming Zone
	No of burners/elements Hotplate type	5 + 1 Black Glass with Metal Frame
Elo	Controls position tric hob	Fascia
	Element 1 (kW)	Warming Zone (0.1)
	Element 2 (kW)	
		Medium (1.8)
	Element 3 (kW)	Small (1.2)
	Element 4 (kW)	Large (2.2)
	Element 5 (kW)	Small (1.2)
	Element 6 (kW)	Medium (1.8)
	Element 7 (kW)	
	Central on/off key Hot hob light	
	Individual residual Heat Indicators	Yes
	Control type (rotary or touch) Digital power display	Rotary No
	Power levels Keep warm function	8 (8+1 Dual Zone) Yes - Warming Zone
	Pan detection	
	Pan overheat detection Child lock	
	Boost function Presets	
	Auto heat up	
	Auto stand by Minute minder	
	Timer Function	
	Bridge Function / Griddle Zone Easy clean ceramic glass surface	No Yes
Cavity 1		

			Top Left
		Position Function	Grill
		Fuel	Electric
		No. of functions	1
		tric oven/grill Variable rate electric grill	Yes
		ty features	
		Actual capacity (litres)	42
		Usable capacity (litres)	33
		Usable Cavity dimensions (HxWxD mm)	183x423x430
		Power (kW) @ 230V	Grill (1.6)
		Energy consumption (Kwh)	N/A
		No of shelves	0
		No of shelf positions	3
		Usable area of shelves (WxD mm)	421x 364
		Oven light / Type Interior finish / colour	N/A Easy clean enamel / Black
	Door		
		Door type	Metal
		Door opening	Drop-down
		Viewing window Door glazing number(inc. outer if applicable)	<u>No</u> x2
		Door colour	Description colour
		Handle style / Colour	Metal, chrome
		Door outer glass	No
		Inner glass	Yes
		Inner Glass Removeable	Yes
Cavi	-		
		Position	Bottom Left
		Main/second/third/fourth oven Function	Second Conventional Oven
		Fuel	Electric
		No. of functions	4
		Programmable oven	No
		oven/grill	
		Fixed rate gas grill Variable rate gas grill	
		Conventional gas oven	
		Automatic ignition	
		Flame safety device	
		tric oven/grill	
		Conventional electric oven Fanned electric oven	Yes
		Defrost/Dough Proving (Combined Function)	
		Light only	Yes
		Slow cook	Yes
		AirFry Function	
		Keep warm/plate warm function Energy rating	Yes A
		ty features	
		Actual capacity (litres)	70L
		Usable capacity (litres)	64L
		Usable capacity (litres) Usable Cavity dimensions (HxWxD mm)	64L 350 x 423 x 413
		Usable capacity (litres)	64L
		Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V	64L 350 x 423 x 413 Oven (2.2)
		Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelf positions	64L 350 x 423 x 413 Oven (2.2) 0.75 3 5
		Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelf positions Usable area of shelves (WxD mm)	64L 350 x 423 x 413 Oven (2.2) 0.75 3 5 421 x 364
		Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelf positions Usable area of shelves (WxD mm) Oven light / Type	64L 350 x 423 x 413 Oven (2.2) 0.75 3 5 421 x 364 Yes, halogen G9
		Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour	64L 350 x 423 x 413 Oven (2.2) 0.75 3 5 421 x 364
	Door	Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour poor type	64L 350 x 423 x 413 Oven (2.2) 0.75 3 421 x 364 Yes, halogen G9 Easy clean enamel / Black Metal/Glass
	Door	Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour Door type Door opening	64L 350 x 423 x 413 Oven (2.2) 0.75 3 421 x 364 Yes, halogen G9 Easy clean enamel / Black Metal/Glass Left Side Opening
	Door	Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour r Door type Door type Door opening Hinge type	64L 350 x 423 x 413 Oven (2.2) 0.75 3 421 x 364 Yes, halogen G9 Easy clean enamel / Black Metal/Glass Left Side Opening Side Opening
	Door	Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelves No of shelves (WxD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes
	Door	Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour r Door type Door type Door opening Hinge type	64L         350 x 423 x 413         Oven (2.2)         0.75         3         421 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Side Opening         Yes         2
	Door	Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           0           1           1           0           1           2           0           1           2           0           2           0           2           0           2           0 <tr td=""></tr>
	Door	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelves No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           2           2           2           2           2           2           Description colour           Metal, chrome
	Door	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour Door type Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door uter glass	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           Q           Description colour           Metal, chrome           Yes x 1
	Door	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelves No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           2           2           2           2           2           2           Description colour           Metal, chrome
	Door	Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour r Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door uter glass Inner glass	64L         350 x 423 x 413         Oven (2.2)         0.75         3         421 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Yes         Q         Yes         Description colour         Metal, chrome         Yes x 1         Yes x 1
	Door	Usable capacity (litres) Usable Cavity dimensions (HxWxD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour Door opening Hinge type Arrest position Viewing window Door oplazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position	64L         350 x 423 x 413         Oven (2.2)         0.75         3         421 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Yes         Question         Yes         Pes x 1         Yes x 1         Yes x 1         Yes         Yes x 1         Yes X 1         Yes
	Door ty 3	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelr positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven	64L         350 x 423 x 413         Oven (2.2)         0.75         3         421 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Side Opening         Yes         Q         Yes         Yes         Yes x 1         Yes x 1         Yes x 1         Yes         Yes         Yes
	Door	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour Toor type Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner glass Inner Glass Removeable Position Main/second/third/fourth oven Function	64L           350 x 423 x 413           Oven (2.2)           0.75           3           41 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           Qes           Yes           Yes 1
	Door	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fuel	64L         350 x 423 x 413         Oven (2.2)         0.75         3         421 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Yes         Question         Yes         Question         Yes x 1         Yes x 1         Yes x 1         Yes X 1         Yes         Yes         Yes         Yes         Yes X 1         Yes X 1         Yes         Y
Cavi	Door ty 3	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner glass Inner glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fuel No. of functions Programmable oven	64L           350 x 423 x 413           Oven (2.2)           0.75           3           41 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           Qes           Yes           Yes 1
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Door colour Door oucer Door oucer Door oucer Door colour Door oucer Door oucer Bass Inner Glass Removeable Position Main/second/third/fourth oven Function Fuel No. of functions Programmable oven Tric oven/grill	64L         350 x 423 x 413         Oven (2.2)         0.75         3         421 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Side Opening         Yes         2         Description colour         Metal, chrome         Yes x 1         Yes x 1         Yes x 1         Yes         Yes         Yes         Yes         Yes x 1         Yes         Yes <t< th=""></t<>
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour Door opening Hinge type Arrest position Viewing window Door opening Hinge type Arrest position Viewing window Door colour Handle style / Colour Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven Fuel No. of functions Programmable oven tric oven/grill Fanned electric oven	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Yes           2           Pess           2           2           2           2           2           2           2           2           2           2           2           2           2           2           2           2           3           3           2           3           3           3           3           4           4           4           4           4           4           4           5           4           5           4           4           4           4           4
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelr positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fuel No. of functions Programmable oven tric oven /grill Fanned electric oven Defrost/Dough Proving (Combined Function)	64L           350 x 423 x 413           Oven (2.2)           0.75           3           41 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Yes           Q           Yes           Q           Yes           Yes           Yes           Yes x 1           Yes x 1           Yes x 1           Yes x 1           Yes           Yes           Yes           Yes           Yes           Yes           Yes           Yes x 1           Yes           Yes           Yes           Yes           Yes           Yes
Cavi	ty 3	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour Door opening Hinge type Arrest position Viewing window Door opening Hinge type Arrest position Viewing window Door colour Handle style / Colour Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven Fuel No. of functions Programmable oven tric oven/grill Fanned electric oven	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Yes           2           Pess           2           2           2           2           2           2           2           2           2           2           2           2           2           2           2           2           3           3           2           3           3           3           3           4           4           4           4           4           4           4           5           4           5           4           4           4           4           4
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven Fuel No. of functions Programmable oven tric oven/grill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFry Function	64L         350 x 423 x 413         Oven (2.2)         0.75         3         41 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Side Opening         Yes         2         Description colour         Metal, chrome         Yes x 1         Yes x 1         Yes x 1         Yes         Yes         Side Oven         Electric         Side Oven         Yes
Cavi	ty 3	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner glass Inner glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fuel No. of functions Programmable oven tric oven/grill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFry Function Keep warm/plate warm function Dough/Bread proving	64L           350 x 423 x 413           Oven (2.2)           0.75           3           41 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           Pess Particle           Yes           Yes           Yes           Yes           Yes           Yes x 1           Yes           Yes           Yes           Yes           Yes           Yes           Yes
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Door oclour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fuel No. of functions Programmable oven tric oven/grill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFry Function Keep warm/plate warm function Dough/Bread proving Energy rating	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           2           Description colour           Metal, chrome           Yes x 1           Yes x 1           Yes           Yes           Side Opening           Yes           2           Pescription colour           Metal, chrome           Yes x 1           Yes x 1           Yes
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door our glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fue No. of functions Programmable oven tric oven/grill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFry Function Keep warm/plate warm function Dough/Bread proving Energy rating ty features	64L         350 x 423 x 413         Oven (2.2)         0.75         3         421 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Side Opening         Yes         Yes         Description colour         Metal, chrome         Yes x 1         Yes S         Yes
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelves No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Yiewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fuel No. of functions Programmable oven tric oven /grill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFry Function Keep warm/plate warm function Dough/Bread proving Actual capacity (litres)	64L         350 x 423 x 413         Oven (2.2)         0.75         3         41 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Side Opening         Yes         Yes         Quert Colour         Yes         Yes X 1         Yes X         Yes X         Xes X 1         Yes X         Xes X 1         Yes X         Xes X         Yes X         Yes X     <
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door our glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fue No. of functions Programmable oven tric oven/grill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFry Function Keep warm/plate warm function Dough/Bread proving Energy rating ty features	64L         350 x 423 x 413         Oven (2.2)         0.75         3         421 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Side Opening         Yes         Yes         Query Yes         Yes x 1         Yes         Yes         Yes x 1         Yes x 1         Yes x 1         Yes         Yes <tr< th=""></tr<>
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour  Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner glass Inner glass Removeable  Position Fuel No. of functions Fuel No. of functions Fuel No. of functions Fuel No. of functions Programmable oven tric oven/prill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFity Function Keep warm/plate warm function Dougl/Bread proving Energy rating ty features Actual capacity (litres) Usable capacity (litres)	64L         350 x 423 x 413         Oven (2.2)         0.75         3         421 x 364         Yes, halogen G9         Easy clean enamel / Black         Metal/Glass         Left Side Opening         Side Opening         Yes         Yes         2         Description colour         Metal, chrome         Yes x 1         Yes x 1         Yes x 1         Yes
Cavi	Door ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fuel No. of functions Programmable oven tric oven / grill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFry Function Keep warm/plate warm function Dough/Bread proving Energy rating ty features Actual capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (KW) @ 230V Energy consumption (Kwh)	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           2           Description colour           Yes x 1           Yes           Yes           Yes           Yes           Yes           Yes           Yes           Yes           Yes
Cavi	ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WxD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner glass Inner glass Inner Glass Removeable Position Fuel No. of functions Fuel No. of functions Fueg No. of functions Fueg No. of functions Fueg No. of functions Fueg No. of functions Fueg No. of functions Fueg No. of functions Fueg Forgarammable oven tric oven/grill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFry Function Keep warm/plate warm function Mable Cavity (litres) Usable Cavity (litres) Usable Cavity (litres) Usable Cavity (litres) Usable Cavity (litres) No of shelves	641           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           2           Description colour           Metal, chrome           Yes X 1           Yes           Yes           Yes           Yes           Yes           Yes           Yes X 1           Yes
Cavi	ty 3 Elect	Usable capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (kW) @ 230V Energy consumption (Kwh) No of shelf positions Usable area of shelves (WXD mm) Oven light / Type Interior finish / colour r Door type Door opening Hinge type Arrest position Viewing window Door glazing number(inc. outer if applicable) Door colour Handle style / Colour Door outer glass Inner Glass Removeable Position Main/second/third/fourth oven Function Fuel No. of functions Programmable oven tric oven / grill Fanned electric oven Defrost/Dough Proving (Combined Function) Slow cook AirFry Function Keep warm/plate warm function Dough/Bread proving Energy rating ty features Actual capacity (litres) Usable Cavity dimensions (HXWXD mm) Power (KW) @ 230V Energy consumption (Kwh)	64L           350 x 423 x 413           Oven (2.2)           0.75           3           421 x 364           Yes, halogen G9           Easy clean enamel / Black           Metal/Glass           Left Side Opening           Side Opening           Yes           2           Description colour           Yes x 1           <

		Oven light / Type	Yes, halogen
	P.	Interior finish / colour	Easy clean enamel / Black
	Door		
		Door type	Metal
		Door opening	Right Side opening
		Hinge type	Side opening
	-	Arrest position Viewing window	Yes No
			x2
		Door glazing number(inc. outer if applicable)	
		Door colour	Description colour
		Handle style / Colour	Metal, chrome
		Door outer glass	No
		Inner glass	Yes
		Inner Glass Removeable	Yes
Cavi	ity 4		
		Position	Bottom Right
		Function	Storage Compartment
	Cavi	ty features	
		Actual capacity (litres)	42L
		Usable capacity (litres)	42L
		Cavity dimensions (HxWxD mm)	350 x 466 x 429
		Interior finish / colour	Easy clean enamel / Black
	Door	r	
		Door type	Metal
		Door opening	Drop Down
		Viewing window	No
		Door colour	Description Colour
	-	Handle style / Colour	Metal, chrome
	-	Cladding type	
		Cladding style / Colour	
Fase			
		ia features	
		Number of knobs	10
		Style of knob - colour & type	Black plastic body, chrome plastic cap
		Bezel - colour & type	textured black plastic
		Oven/Grill markings location (knob, bezel, facia)	White print, on bezel
		Fascia material	Metal one piece pressing
		Fascia colour	Description colour
		Fascia cooling system	Yes
		Screened Branding or Model Name	Farmhouse
Time	er		
		Touch control clock/programmer - cavity, size and colour	Cavity 2, large, white
Feat	tures		
		Adjustable feet	Yes
		Rear wheels	Yes
Acce	essor	ies (included)	
		Full width oven/grill pan - deep	Yes x1
		Full width oven/grill pan - trivet	Yes x1
		Oven/grill pan handle	Yes x1
		AirFry Tray	Yes x1
Rem	novab	ble Parts (for cleaning)	
		Inner door glass	Yes
		Shelves	Yes
		Sherves	
		Shelf guides	Yes
Inst	tallati	Shelf guides on	
Inst	tallati	Shelf guides on LPG convertible	No
Inst	tallati	Shelf guides on LPG convertible Hard wired	No Yes
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length	No Yes N/A
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position	No Yes N/A Middle left
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection	No Yes N/A Middle left Terminal block
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage	No           Yes           N/A           Middle left           Terminal block           230/400V
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No
Inst	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply requency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           No           N/A
	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No
	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ms	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           No           N/A
	tallati	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ms ted	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           No           N/A           650mm
	ensio Pack	Shelf guides on DPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns ed Height (mm)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           N/A           650mm           975
	ensic	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ons eed Height (mm) Width (mm)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15:3           32 A           No           N/A           650mm           975           1060
	ensic	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns red Height (mm) Width (mm) Depth (mm)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           22 A           No           650mm           975           1060           714
	eensid	Shelf guides on UPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns sed Height (mm) Width (mm) Depth (mm) Weight (kg)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15:3           32 A           No           N/A           650mm           975           1060
	ensic	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ons ted Height (mm) Width (mm) Depth (mm) Weight (kg) Let	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           N/A           650mm           975           1060           714           100
	eensid	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ons eed Height (mm) Weight (kg) Uet Height (mm)	No           Yes           N/A           Middle left           Terninal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           N/A           650mm           975           1060           714           900-930
	eensid	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns red Height (mm) Width (mm) Weight (kg) Uct Height (mm) Width (mm) Width (mm)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           23.4           No           N/A           650mm           975           1060           714           100           990-930           996
	ensid Pack	Shelf guides on DFG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns ed Height (mm) Width (mm) Depth (mm) Width (mm) Width (mm) Depth (mm)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           N/A           650mm           975           1060           714           100           990-930           996           600
Dim	ensid Pack	Shelf guides on DECOMPTIGNESS Shelf guides Shelf guides On LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) Decompt (mm) Width (mm) Uidth (mm) Uidth (mm) Weight (kg) Uidth (mm) Depth (mm) Weight (kg)	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           23.4           No           N/A           650mm           975           1060           714           100           990-930           996
Dim	eensid Pack	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ons ed Height (mm) Depth (mm) Weight (kg) Weight (kg) Weight (kg) Be codes	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           22.A           No           NA           650mm           975           1060           714           900-930           996           600           86.932
Dim	ensid Pack	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns red Height (mm) Width (mm) Depth (mm) Weight (kg) Width (mm) Depth (mm) Weight (kg) & codes u 1	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           NA           650mm           975           1060           714           100           990-930           996           600           86.932           Anthracite
Dim	eensid Pack	Shelf guides on DFG convertible LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns ced Height (mm) Width (mm) Depth (mm) Width (mm) Depth (mm) Weight (kg) ar of securing to mail to the securing of the securing to the securing of the securing to the securing	No           N/A           N/A           Middle left           Terninal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           N/A           650mm           975           1060           714           100           900-930           996           600           86.932
Dim	eensid Pack	Shelf guides on DECOMPTYCAL De	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           2.2 A           No           N/A           650mm           975           1060           714           100           900-930           996           600           86.932           Anthracite           444411825           5052263118256
Dim	ensio Prod	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ons ed Height (mm) Depth (mm) Depth (mm) Weight (kg) uct Height (mm) Weight (kg) Weight (kg) Weight (kg) Method (mm) Depth (mm) Method (mm) Depth (mm) Method (mm) Secodes ur 1 SKU code EAN code AS400/Aurora model description	No           N/A           N/A           Middle left           Terninal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           N/A           650mm           975           1060           714           100           900-930           996           600           86.932
Dim	ensio Prod Shes i Colo	Shelf guides on DFG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns ed Height (mm) Width (mm) Depth (mm) Width (mm) Depth (mm) Weight (kg) a codes a r 1 SKU code EAN code AS400/Aurora model description Exclusive	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           32.A           No           N/A           650mm           975           1060           714           100           990-930           996           600           86.932           Anthracite           444411825           5052263118256           BEL RCA FARMHOUSE 100E ANT
Dim	ensio Prod	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ons ted Height (mm) Width (mm) Depth (mm) Weight (kg) Uuct Height (kg) Weight (kg) Weight (kg) Weight (kg) Weight (kg) SKU code EAN code EAN code AS400/Aurora model description Exclusive Ur 2	No           Yes           N/A           Middle left           Terninal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           N/A           650mm           975           1060           714           100           900-930           6600           600           86.932           Anthracite           444411825           5052263118256           BEL RCA FARMHOUSE 100E ANT
Dim	ensio Prod Shes i Colo	Shelf guides on LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ons eed Height (mm) Width (mm) Depth (mm) Weight (kg) uct Height (mm) Width (mm) Depth (mm) Weight (kg) Exclose LAN code AS400/Aurora model description Exclusive ur 2 SKU code	No           Yes           N/A           Middle left           Terminal block           230/400V           30/60 Hz           315.3           32 A           No           No           N/A           650mm           975           1060           714           100           900-930           996           600           86.932           444411825           5052263118256           BEL RCA FARMHOUSE 100E ANT           BEL RCA FARMHOUSE 100E ANT
Dim	ensio Pack	Shelf guides         on         LPG convertible         Hard wired         Lead length         Terminal block position         Electrical connection         Supply voltage         Supply frequency         Phase (single or 3)         Total electrical power load (kW) @230V         Minimum Electrical Connection Rating (A)         Fitted 3 pin plug         Method of securing to wall (stability bracket/safety chain)         Minimum distance required above (mm)         nns         ced         Height (mm)         Width (mm)         Weight (kg)         ueth         Height (kg)         width (mm)         Weight (kg)         & codes         ur 1         SkU code         EAN code         EAN code         SkU code         EAN code	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           223 A           No           No           650mm           650mm           975           1060           714           100           990-930           996           600           86.932           Anthracite           444411825           5052263118256           BEL RCA FARMHOUSE 100E ANT           Black           444411826           5052263118263
Dim	ensio Prod Prod Shes i Colo	Shelf quides         on         LPG convertible         Hard wired         Lead length         Terminal block position         Electrical connection         Supply voltage         Supply frequency         Phase (single or 3)         Total electrical power load (kW) @230V         Minimum Electrical Connection Rating (A)         Fitted 3 pin plug         Method of securing to wall (stability bracket/safety chain)         Minimum distance required above (mm)         ns         ed         Height (mm)         Width (mm)         Depth (mm)         Weight (kg)         uct         Height (kg)         & codes         wr 1         SKU code         EAV0/Aurora model description         Exclusive         ur 2         SKU code         EAV00/Aurora model description	No           Yes           N/A           Middle left           Terminal block           230/400V           30/60 Hz           315.3           32 A           No           No           N/A           650mm           975           1060           714           100           900-930           996           600           86.932           444411825           5052263118256           BEL RCA FARMHOUSE 100E ANT           BEL RCA FARMHOUSE 100E ANT
Dim	ensic Prod	Shelf guides on DFG convertible LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns ced Height (mm) Width (mm) Depth (mm) Weight (kg) Uuct Height (mm) Width (mm) Depth (mm) Weight (kg) ExCuse SKU code EAN code AS400/Aurora model description Exclusive UUC	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           22 A           No           N/A           650mm           975           1060           714           100           900-930           900-930           660           600           86.932           Anthracite           444411825           5052263118256           BEL RCA FARMHOUSE 100E ANT           BLaCK           444411826           5052263118263           BEL RCA FARMHOUSE 100E BLK
Dim	ensio Prod Prod Shes i Colo	Shelf quides on EPG convertible LPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ons ed Height (mm) Width (mm) Depth (mm) Width (mm) Depth (mm) Width (mm) Depth (mm) Width (mm) Edets EAN code Catuation Catu	No           Yes           N/A           Middle left           Terminal block           230/400V           30/60 Hz           32 A           No           No           No           N/A           650mm           650mm           975           1060           714           100           900-930           996           600           86.932           Anthracite           444411825           5052263118256           BEL RCA FARMHOUSE 100E ANT           BEL RCA FARMHOUSE 100E BLK           444411826           5052263118263           BEL RCA FARMHOUSE 100E BLK
Dim	ensic Prod	Shelf guides on PG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ms ed Height (mm) Weight (kg) Uct Height (mm) Weight (kg) Width (mm) Depth (mm) Weight (kg) Uct SKU code EAN code AS400/Aurora model description Exclusive Ur 3 SKU code Exclusive Ur 3 SKU code Extra code SKU code Extra code SKU code Extra code SKU code SK	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           24           No           No           No           NA           650mm           650mm           975           1060           714           100           990-930           996           600           86.932           S052263118256           BEL RCA FARMHOUSE 100E ANT           Black           444411826           5052263118263           BEL RCA FARMHOUSE 100E BLK
Dim	ensic Prod	Shelf quides on UPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical power load (kW) @230V Minimum Electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ns ed Height (mm) Width (mm) Depth (mm) Weight (kg) Uct Height (kg) Ku code EAN code AS400/Aurora model description Exclusive Ur 3 SKU code EAN code E	No           Yes           N/A           Middle left           Terninal block           230/400V           50/60 Hz           3 Phase           15.3           32 A           No           N/A           650mm           975           1060           714           100           900-930           900-930           900-930           996           600           86,932           Subtracte           444411825           5052263118256           BEL RCA FARMHOUSE 100E ANT           BEL RCA FARMHOUSE 100E BLK           Cream           444411827           5052263118270
Dim	ensic Prod	Shelf guides on EPG convertible Hard wired Lead length Terminal block position Electrical connection Supply voltage Supply frequency Phase (single or 3) Total electrical Connection Rating (A) Fitted 3 pin plug Method of securing to wall (stability bracket/safety chain) Minimum distance required above (mm) ms ed Height (mm) Weight (kg) Uct Height (mm) Weight (kg) Weight (kg) Weight (kg) SKU code EAN code AS400/Aurora model description Exclusive Ur 3 SKU code	No           Yes           N/A           Middle left           Terminal block           230/400V           50/60 Hz           3 Phase           15.3           24           No           No           No           NA           650mm           650mm           975           1060           714           100           990-930           996           600           86.932           S052263118256           BEL RCA FARMHOUSE 100E ANT           Black           444411826           5052263118263           BEL RCA FARMHOUSE 100E BLK